



DD-4S/A

Simultaneous 4-channel charging for all the 4 channels. Charging of Li-ion battery is done through V-Mount/Gold Mount plate. LCD screen shows the charging status of each channel precisely, such as instantaneous voltage, current of the battery, and the capacity that has been charged on the charger.

DD-4S for V-Mount batteries
DD-4A for Gold Mount batteries

Input	AC 90V~240V/47Hz~63Hz
Charger Output	DC 16.8V/2.5A
Dimension	290x145x175mm
Weight	3.80Kg



D-4S/A

4-channel charger with adapter. Charging of Li-ion battery is done through V-Mount/Gold Mount plate. Simultaneous 4-channel charging for all the 4 channels. Charger and adapter function can't work at the same time.

D-4S for V-Mount batteries
D-4A for Gold Mount batteries

Input	AC 90V~240V/47Hz~63Hz
Charger Output	DC 16.8V/2.5A
Adapter Output	DC 15.0V/4.0A
Dimension	248x132x195mm
Weight	2.48Kg



D-2S/A

Simultaneous 2-channel charging for both channels. Charging of Li-ion battery is done through V-Mount/Gold Mount plate. It can also be used as DC adapter, charger and adapter function can work at the same time. Adapter output is 16.2V 4.0A. Universal AC input voltage for worldwide operation.

D-2S for V-Mount batteries
D-2A for Gold Mount batteries

Input	AC 90V~240V/47Hz~63Hz
Charger Output	DC 16.8V/2.6A
Adapter Output	DC 16.2V/4.0A
Dimension	231x141x60.5mm
Weight	1.00Kg



D-2SN/AN

Simultaneous 2-channel charging for both channels. Charging of Li-ion battery is done through V-Mount/Gold Mount plate. Universal AC input voltage for worldwide operation.

D-2SN for V-Mount batteries
D-2AN for Gold Mount batteries

Input	AC 90V~240V/47Hz~63Hz
Charger Output	DC 16.8V/2.6A
Dimension	231x141x60.5mm
Weight	1.00Kg



DS-2S/A

2-channel charger with adapter, V-Mount and Gold Mount.

Charger and adapter function can work simultaneously.

Simultaneous 2-channel charging for both channels.

Integrated 50W DC power supply provides 50W XLR output for the camera, lighting or ancillary broadcast devices.

Inhibit IC protection system to prevent over current, voltage and short circuit.

DS-2S for V-Mount batteries
DS-2A for Gold Mount batteries

Input	AC 90V~240V/47Hz~63Hz
Charger Output	DC 16.8V/2A
Adapter Output	DC 14.8V/3.3A
Dimension	215x85x155mm
Weight	1.30Kg



D-TRAVEL

D-TRAVEL charger can charge all our batteries with B port directly.

Ultra portable.

Single charger.

Charge through D-tap.

Input	AC 90V~240V/47Hz~63Hz
Charger Output	DC 16.8V/1.8A
Power	Max 35W
Applicable battery	Battery with D-tap socket
Dimension	120x60x38mm
Weight	0.25Kg



DDBC-TF

Dual Digital Battery Charger for SONY L series DV camcorder batteries.

Input	AC 90V~240V/47Hz~63Hz,DC 12-24V/3A(MAX)
Charger Output	Output Charging:8.4V,USB Output:5V 2A
Output Charging Current	L:1.0Ax1 0.5Ax2 / H:1.5Ax1 0.8Ax2
Applicable	Dynacore DV-2S,DV-4S,DV-6S SONY NP-F550/770/970
Dimension	122x110x34mm
Weight	0.40Kg



DDBC-TP

Dual Digital Battery Charger for Panasonic CGA series DV camcorder batteries.

Input	AC 90V~240V/47Hz~63Hz,DC 12-24V/3A(MAX)
Charger Output	Output Charging:8.4V,USB Output:5V 2A
Output Charging Current	L:1.0Ax1 0.5Ax2 / H:1.5Ax1 0.8Ax2
Applicable	Dynacore DV-66S Panasonic CGA-D16S/28S/54S
Dimension	122x110x34mm
Weight	0.40Kg



DDBC-TU

Dual Digital Battery Charger for Sony BP-U30/U60/U90 batteries.

Input	AC 90V~240V/47Hz~63Hz,DC 12-24V/3A(MAX)
Charger Output	Output Charging:16.8V,USB Output:5V 2A
Output Charging Current	L:1.0Ax1 0.5Ax2 / H:1.5Ax1 0.8Ax2
Applicable	Dynacore DS-U77,DS-U77B SONY BP-U30/60/U90
Dimension	122x110x34mm
Weight	0.40Kg



4-channel charger designed for professional DV batteries.
 It can charge 4 batteries simultaneously.
 DV-FSP is the charger for Dynacore DV-2S/4S/6S/66S.
 DV-FU is the charger for Dynacore DS-U77&DS-U77B.



DV-FSP

Mount plate for DV-FSP is universal for SONY NP-F550/770/970 Panasonic CGA-F16S/28S/54S. It can charge these different model batteries at the same time.



Specifications:

Input	AC 90V~240V/47Hz~63Hz
Charger Output	DC 8.4V/2.0A
Dimension	210x138x77mm
Weight	1.20Kg
Applicable	Dynacore DV-2S,DV-4S,DV-6S,DV-66S
	SONY NP-F550/770/970
	Panasonic CGA-D16S/28S/54S



DV-FU

Mount plate for the DV-FU, 4 batteries can be charged at the same time.



Specifications:

Input	AC 90V~240V/47Hz~63Hz
Charger Output	DC 16.8V/1.5A
Dimension	230x170x73mm
Weight	1.45Kg
Applicable	Dynacore DS-U77,DS-U77B
	SONY BP-U30/60/U90

