

DSR Series Fluorescent Soft Light



- Soft, even, smooth light field free of exposure of heat from the beam emission.
- High light output from the luminaries with high efficiency reflector and barn door.
- High color rendering index (CRI up to 85-95). Optimum effects shall be expected when the luminary use halogen lamps.
- High illumination of lamp tubes (70-80 lumens/watt) and longer lamp life (imported lamps rated more than less than 10000 hours).
- Energy-saving components utilized to save electrical energy by 70%.
- Lamp holders mounted meet international safety standards; imported electronic ballasts are used for lower noise and reliable operations.
- Added dimming function optional with imported ballasts enabling a wide dimming range while maintaining a constant color temperature.
- Ideal for lighting applications for medium and small-sized studios and conference rooms as well as news studios.

Specification:

Item No.	Power Input	Spigot	Wattage	Color Temperature	Dimming	Dimensions	Weights
DSR 36x2	AC 100-240V,50/60Hz	Φ28x75	72W	3200°K/5600°K		480x240x150mm	4.75Kg
DSRIV 36x2	AC 100-240V,50/60Hz	Φ28x75	72W	3200°K/5600°K	Dimmer Rack	480x240x150mm	4.77Kg
DSR 36x4	AC 100-240V,50/60Hz	Φ28x75	144W	3200°K/5600°K		480x365x150mm	6.85Kg
DSRIV 36x4	AC 100-240V,50/60Hz	Φ28x75	144W	3200°K/5600°K	Dimmer Rack	480x365x150mm	6.87Kg
DSR 36x6	AC 100-240V,50/60Hz	Φ28x75	216W	3200°K/5600°K		480x520x150mm	9.30Kg
DSRIV 36x6	AC 100-240V,50/60Hz	Φ28x75	216W	3200°K/5600°K	Dimmer Rack	480x520x150mm	9.32Kg
DSR 55x2	AC 100-240V,50/60Hz	Φ28x75	110W	3200°K/5600°K		605x240x150mm	5.70Kg
DSRIV 55x2	AC 100-240V,50/60Hz	Φ28x75	110W	3200°K/5600°K	Dimmer Rack	605x240x150mm	5.72Kg
DSR 55x4	AC 100-240V,50/60Hz	Φ28x75	220W	3200°K/5600°K		605x365x150mm	7.90Kg
DSRIV 55x4	AC 100-240V,50/60Hz	Φ28x75	220W	3200°K/5600°K	Dimmer Rack	605x365x150mm	7.92Kg
DSR 55x6	AC 100-240V,50/60Hz	Φ28x75	330W	3200°K/5600°K		605x645x150mm	10.40Kg
DSRIV 55x6	AC 100-240V,50/60Hz	Φ28x75	330W	3200°K/5600°K	Dimmer Rack	605x645x150mm	10.42Kg